



IPS-14RS Syringe Pump

Independent Dual Channel Infusion/Withdrawal Pump with Recipe Management

The IPS-14RS combines bidirectional flow and recipe management across two completely independent channels. Users can save up to 5 recipes and run up to 50 repeat cycles automatically. It is the most advanced and versatile model in the IPS-14 series.

- 4.3" interactive touch display
- Independent bidirectional control with recipe management
- Supports 5 recipes and 50 repeat cycles for each channel

SYRINGES

CAPACITY	2 Independent
TYPE	Glass, plastic, steel
MIN SIZE	Hamilton 0.5 µl (ID:0.103mm)
MAX SIZE	Monoject 140 ml (ID:38mm)

FLOW RATE

MIN	17,89 µl/min (Hamilton 0.5 µl)
MAX	121,51 ml/min (140 ml Monoject Syringe)
ACCURACY	< 1%
REPRODUCIBILITY	< 1%

MOTOR SPESIFICATIONS

MOTOR TYPE	Stepper Motor
MOTOR DRIVE CONTROLLER	Microcontroller with Microstep Drive
STEP RESOLUTION (TRAVEL/MICROSTEP)	357 nm/µstep
MIN STEP RATE	10 sec/µstep
MAX STEP RATE	200 µsec/µstep
MIN LINEAR SPEED	2,14 µm/min
MAX LINEAR SPEED	107,14 µm/min
LINEAR FORCE	20 kg for each syringe

GENERAL SPESIFICATIONS

RECIPE SAVE-RECALL	Yes
POWER SUPPLY	12 VDC 1A (110-240 VAC adapter included)
DIMENSIONS	W:211 L:257 H:137 mm
WEIGHT	3.6 kg

OPERATING CONDITIONS

OPERATING TEMPERATURE	Between -10 and 50 (°C)
STORAGE TEMPERATURE	Between -30 and 85 (°C)
OPERATING HUMIDITY	RH 10% - RH 90% (not condensed)
STORAGE HUMIDITY	RH 10% - RH 90% (not condensed)