

P-21 Peristaltic Pump Specifications



P-21 Peristaltic Pump

Multi-channel peristaltic pump for precise and reliable fluid transfer

- Multiple-Channel Operation
- Accurate, Pulse-Free Flow
- Chemical-Resistant Construction

- Multi-channel operation (up to 6 channels)
- 4.3" Color TFT Touchscreen Interface
- Microprocessor software for automated control
- Adjustable flow rate during process
- Learn & Repeat Mode and Recipe Save & Recall
- Reversible flow for quick cleaning

FLOW RATE

SPEED RANGE	1-100 rpm
SPEED RESOLUTION	1 rpm
FLOW RATE	Up to 48 ml/min per channel
FLOW CALIBRATION MODE	Available

MOTOR SPESIFICATIONS

MOTOR TYPE	Stepper Motor
CONTROL SYSTEM	Microprocessor-based controller
DIRECTION	Reversible (forward/reverse)
OPERATION MODES	Continuous / Timed / Volume-based
LEARN & REPEAT MODE	Available
RECIEPE SAVE & RECALL	Available
FAST-RUN MODE	Available

CONSTRUCTION & MATERIALS

PUMP HEAD HOUSING	PPS (Polypheneylene Sulfide)
ROLLERS	304 Stainles steel
BODY MATERIAL	Powder-coated steel
CHEMICAL RESISTANCE	Heat, solvent, corrosion, and flame resistant
CARTRIDGE TYPE	Ratchet type
CHANNEL NUMBER	6 Max
TUBING SIZE	ID ≤ 3.17 mm (0.8-1.0 mm wall thickness)

OPERATING CONDITIONS

OPERATING TEMPERATURE	0-40 (°C)
OPERATING HUMIDITY	< 80 % RH (non-condensed)
STORAGE HUMIDITY	-10 – 60 °C